

eco-pave block sealer

Solvent Free Surface Sealer

Description eco-pave block sealer is a clear, solvent free acrylic resin coating used to seal and protect patios, paths, natural stone, concrete and block paving (and other hard landscaped areas) from the effects of sunlight, water, oil, petrol and lichen growth. The result is a hard wearing water repellent film which has a low sheen, slip resistant finish.

- Advantages**
- Prevents the appearance of green mould
 - Prevents sand loss from joints and weed growth, lichen, moss & grass
 - Reduces penetration of oil, fuels & reduces staining
 - Hard wearing, durable and long lasting
 - One component system
 - Good UV resistance

Application All Surfaces must be free from grease, dust, loose material, lichen etc. The surface to be treated should be cleaned with a fungicidal wash, should there be heavy staining such as oil or grease this should be treated with a heavy duty degreasant.

A nominal coverage rate of 8m²/litre per coat can be achieved , however, since the porosity and profile of surfaces can vary extensively we recommend that a test area be carried out to determine the actual coverage rate for each job.

eco-pave block sealer must be stirred before use and may be applied to damp, but not wet, surfaces with a long pile roller or low pressure sprayer, ensuring an even, thorough

Coverage. Care should be taken to avoid ponding. Normally applied as a two coat system. If required a third coat can be applied but it should be noted that this will increase the sheen to a semi-gloss finish. Drying time between coats is approximately 4 Hours at 20°C. Equipment should be cleaned with warm water immediately after use.

Technical Data	Appearance	White Emulsion
	Flash Point (PMCC)	>100°C
	Freezing Point	-2°C
	Coverage Rate	8m ² / litre per coat approximate
	Drying Time (Between Coats)	4 hours at 20°C.
	Shelf Life (sealed container)	12 Months

Limitations

- Do not apply below 5°C (air or surface temperature)
- eco-pave block sealer should not be used on surfaces that have been previously treated with other water proofing solutions such as Silicone or Stearate Based Treatments unless the surface has weathered to such an extent that no water beading effects are observable.
- Use only as directed. Store only in the original container.
- eco-pave block sealer should not be used if rain is expected within 5 hours of application.
- Dispose of the product and packaging correctly.
- Do not allow to enter watercourses.
- Areas treated with eco-pave block sealer should be cleaned with warm water and detergent—Never use acid based cleaners or pressure washing systems.

Health & Safety

When working with eco-pave block sealer suitable protective clothing, eye/face protection and gloves should be worn.

For further health and safety information, please refer to the relevant Safety Data Sheet

Packaging

eco-pave block sealer is available in 5 and 20 Litre Containers.

Storage

eco-pave block sealer should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least six months.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.