

## eco-wallseal

Solvent Free Water Repellent Penetrating Sealer

---

**Description** eco-wallseal is a high performance clear, solvent free water repellent specially formulated to prevent water penetration to brick, stone, concrete, pebbledash, rendering and other mineral substrates. Logco eco-wallseal penetrates deeply into the surface treated to provide effective long term water repellence, is unaffected by ultra violet light and offers superior water beading

---

**Advantages**

- May effect the substrate appearance for a short period
- An effective water repellent for use on concrete, brick, stone, render and pebble-dashing.
- Provides improved durability and beading effect.
- A solvent free, environmentally friendly product.
- Non-flammable.
- Easily applied by low pressure spray equipment.
- May be applied to damp surfaces.

---

**Limitations**

- eco-wallseal should not be applied below 10°C
- Do not apply when raining or when rain is imminent
- Do not use on painted surfaces
- eco-wallseal should not be used on painted surfaces, wood, plastic or rubber.
- Allowing the first coat to dry may prevent penetration of the second coat, always apply the second coat within 1 hour, or before the first coat is dry.
- Do not use in fishponds
- Do not use detergents to clean the substrate prior to use of eco-wallseal as it will dramatically reduce the beading effect.

---

<b>Technical Data</b>	Appearance	Milky white –dries clear
	Composition	Emulsified polysiloxane resin in water
	Average Coverage	5-8m <sup>2</sup> /litre
	Shelf Life (sealed container)	12 months minimum

## Application

All surfaces to be treated must be clean, sound, free from dirt, mould, algae, grease or other contaminants—they may be damp but must be free of standing water. Any necessary repairs should be carried out before application of eco-wallseal .

eco-wallseal is supplied ready for use but must be shaken well before use and can be applied by brush, spray or roller.

When applying on vertical surfaces it should be applied from the bottom up.

Ensure the whole area to be treated is saturated, any puddling should be addressed 15-20 minutes after initial application.

eco-wallseal is applied as a two coat system, the second coat being applied whilst the first coat is still wet— within 1 hour of initial application.

---

## Health & Safety

When working with eco-wallseal suitable protective clothing, eye/face protection and gloves should be worn.

For further health and safety information, please refer to the relevant Safety Data Sheet

---

## Packaging

eco-wallseal is available in 5 and 20 Litre Containers.

---

## Storage

eco-wallseal should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

---

## Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.