

eco-cure super

*Water Based high efficiency (90%)
Curing Membrane for Concrete*



Advantages

- Reduces surface shrinkage and cracking by controlling moisture.
- Provides a strengthened concrete.
- Dustproofs
- Non toxic and non flammable.
- No need for damp hessian or polythene.

Application

- ▲ Always stir or shake **eco-cure super** before use.
- ▲ Apply using a fine spray onto newly placed concrete
- ▲ The surface should be free from surface water.
- ▲ Coverage rate—4-6m² per litre.
- ▲ All equipment should be cleaned with water.
- ▲ Eco-cure super does not fall within the scope of BS7542:1992 but has approx a 90% curing efficiency.

Product Description

eco-cure super is a spray on temporary membrane to retain moisture in freshly placed concrete.

It is formulated to prevent evaporation of the gauging water and provides an efficient method for curing concrete. Gives reduced shrinkage and cracking and creates a more durable, hard wearing surface.

Technical Data

Appearance	White liquid
Curing Efficiency	> 90% at 6m ² /litre
Specific Gravity @ 15.6c	1.01 (approx)
Flash Point (PMCC)	> 100°C
Drying Time @ 20°C	Tack Free— 2 to 4 hours Hard Dry— 18 to 24 hours
Shelf Life (sealed container)	12 months minimum
Compliance	ASTM C-309, Type1, Class A&B

eco-cure super

Health & Safety

- ▲ When working with **eco-cure super** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ For further health and safety information, please refer to the relevant Safety Data Sheet.

Packaging

eco-cure super is available in 5, 20, 25 and 200 Litre Containers.

IBC's available on request.

Storage

eco-cure super should be stored under dry, frost-free

conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the

actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Technical Helpline

Tel: 0113 216 8822
e-mail: technical@logco.co.uk

Sales Team

Tel: 0113 216 8822
e-mail: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd

Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK
Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: sales@logco.co.uk, technical@logco.co.uk
www.logco.co.uk/



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour

involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.