



eco-lease MR2

*Environmentally Friendly Biodegradable
Chemical Release Agent*

Product Description

eco-lease MR2 is a readily biodegradable chemical release agent specially formulated to give easy release from pre-cast moulds or formwork and provides a high quality surface finish to concrete. A low viscosity blend of vegetable oils giving a safe, low odour and non staining mould oil.

Advantages

- Non-hazardous and biodegradable.
- Ideal for use on all types of formwork and pre-cast moulds.
- A highly mobile liquid that is suspension and sediment free and as such can be used in very fine spray nozzles without clogging.
- Has no unpleasant odour.
- Is extremely economical due to the high coverage rates.
- Is highly mobile, even at low temperatures.
- May be applied to the formwork either prior to casting or after the formwork has been left until dry.
- The natural chemical reaction between eco-lease MR2 and the concrete promotes a uniform, matt, stain free concrete surface free from blow holes and surface blemishes.
- Repeated use of eco-lease MR2 gives progressively better results from timber formwork.
- Is suitable for use with both grey and white cements.
- Provides a quick release of the formwork, reducing labour costs and damage to moulds.

Technical Data

Appearance	Low viscosity clear yellow liquid
Specific Gravity @ 15.6c	0.854
Flash Point (PMCC)	>85°C
Viscosity	Non viscous
Solubility in water	Non soluble
Average Coverage	30-40m ² /litre
Shelf Life (sealed container)	12 months minimum

Application

- eco-lease MR2 is supplied ready for use. It should never be diluted and should be applied as thinly and evenly as possible in order to optimise its performance.
- eco-lease MR2 can be applied to all types of formwork by spray, brush, swab or roller—best results are achieved by low pressure spray equipment. Any excess should be removed by swab.
- If using eco-lease MR2 on new or unsealed timber formwork pre-treatment is recommended with a second coat applied prior to use.
- eco-lease MR2 should be applied in well ventilated areas.

eco-lease MR2

Health & Safety

- ▲ When working with **eco-lease MR2** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ For further health and safety information, please refer to the relevant Safety Data Sheet.

Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Packaging

eco-lease MR2 is available in 20, 25 and 200 Litre Containers.

IBC's available on request.

Storage

eco-lease MR2 should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline

Tel: **0113 216 8822**
e-mail: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team

Tel: **0113 216 8822**
e-mail: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd

Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK

Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: sales@logco.co.uk, technical@logco.co.uk

www.logco.co.uk



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.