

logco Aquaseal 102

*Hydrophobic impregnating
silane-based water repellent.*



Product Description

logco Aquaseal 102 is a solvent based, hydrophobic impregnating agent based on a silane resin solution.

logco Aquaseal 102 penetrates into the pores of the surface being treated, forming a silicone resin in situ which imparts water repellent properties to nearly all building surfaces.

logco Aquaseal 102 is not film forming and hence will not affect the appearance or water diffusion capacity of the substrate. Protects bridges and other structures from salt spray.

Technical Data

Appearance	Low viscosity clear liquid
Specific Gravity @ 15.6c	0.804
Flash Point (PMCC)	38°C min
Viscosity cSt @ 40°C	N/A
Coverage exposed location	3-6m ² per litre
Coverage sheltered location	10-15m ² per litre
Recommended dilution	None required

Advantages

- Single coat application.
- Easy to apply by non-atomising spray, brush or roller.
- Allows treated surfaces to breathe.
- Minimal effect to surface appearance.
- Protects from ingress of water-borne ions, such as chlorides and sulphates.
- Improves freeze/thaw resistance of treated surfaces.
- Reduces susceptibility to corrosion of reinforcements.

Application

- ▲ Use only in dry weather and in well ventilated conditions.
- ▲ Surfaces must be absolutely dry.
- ▲ Never use an atomising spray on wet or damp surfaces nor at temperatures below 3°C.
- ▲ Apply generously by brush, roller or non-atomising spray.
- ▲ Drying time at 20°C will be about 2 hours.

logco Aquaseal 102

Health & Safety

- ▲ When working with **logco Aquaseal 102** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ For further health & safety information, please refer to the relevant Safety Data Sheet.

Packaging

logco Aquaseal 102 is available in 5, 25 and 200 litre containers.

Packaged in metal containers. IBC's available on request.

Storage

Unopened containers of **logco Aquaseal 102** should be stored in metal containers under dry,

frost-free conditions away from direct sunlight. Under such conditions the shelf life is at least twelve months.

Once opened replace lid immediately after use and use within 2 weeks.

Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual

conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Special Note

If the concrete being treated is dense, **logco Aquaseal 102** will only penetrate up to 1mm. Hence will not be particularly resistant to weathering.

In such cases applying a coat of *logco Hardseal* over the Aquaseal will protect the coating with its acrylic resin film.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline

Tel: 0113 216 8822
e-mail: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team

Tel: 0113 216 8822
e-mail: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd

Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK
Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: sales@logco.co.uk, technical@logco.co.uk
www.logco.co.uk



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.