

# logco Hardseal

*High Performance, Heavy Duty  
Acrylic Sealer*



## Product Description

**logco Hardseal** is a low viscosity, penetrating colourless sealer and is based on a carefully sourced blend of chemicals. It hardens, cures and seals. Unaffected by water, oil and many common chemicals.

**logco Hardseal** will greatly increase concrete surface anti-abrasion properties particularly on warehouse\factory floors, concrete carriageways and spillway aprons.

## Technical Data

Appearance	Low viscosity clear liquid
Specific Gravity @ 15.6c	0.911
Flash Point (PMCC)	43°C
Viscosity cSt @ 40°C	N/A
Coverage	5-12 m2 per Litre
Recommended dilution	None required

## Advantages

- Protects many surfaces from abrasion and water and oil penetration.
- Consolidates floor surfaces.
- Can be used on both interior and exterior brickwork, masonry, reinforced concrete, concrete floors floor screeds, pavements and car parks.
- Single component, ie no mixing involved.
- Can be used both internally and externally.

## Application

- ▲ **logco hardseal** is supplied as a ready to apply product by brush or non-atomising spray. Do not over apply and brush out any runs that may occur. After about 20 minutes the sealer should have soaked into the concrete, and then further coats should be applied until no more material is absorbed.
- ▲ Allow 2 to 3 hours to elapse between coatings. Normally 2 coatings are sufficient but on 3 coatings may be needed on very porous surfaces.
- ▲ Use only in well ventilated areas and away from sources of ignition.

# logco Hardseal

## Health & Safety

- ▲ When working with **logco Hardseal** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ Areas where this product is being applied must be well ventilated.
- ▲ For further health and safety information, please refer to the relevant Safety Data Sheet.

## Packaging

**logco Hardseal** is available in 5 , 20, 25 and 200 Litre Containers. IBC's available on request.

## Storage

**logco Hardseal** should be stored under dry, frost-free

conditions away from direct sunlight, under such conditions the shelf life is at least twelve months, if unopened.

Once opened replace lid immediately after use and use within 2 weeks.

## Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company. It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in

the light of our continual research and development programme the information relating to each product has not been superseded.

### Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

### Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

#### Technical Helpline

Tel: **0113 216 8822**  
e-mail: [technical@logco.co.uk](mailto:technical@logco.co.uk)

#### Sales Team

Tel: **0113 216 8822**  
e-mail: [sales@logco.co.uk](mailto:sales@logco.co.uk)

#### Leeds Oil & Grease Co. Ltd

Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK  
Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: [sales@logco.co.uk](mailto:sales@logco.co.uk), [technical@logco.co.uk](mailto:technical@logco.co.uk)  
[www.logco.co.uk](http://www.logco.co.uk)



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy

himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.