

logco-lease QD

Quick Drying Chemical Release Agent



Product Description

logco-lease QD is an extremely versatile quick drying high specification chemical release agent specially blended to give optimum release resulting in high class concrete finishes from most types of formwork.

Technical Data

Appearance	Low viscosity clear amber liquid
Specific Gravity @ 15.6c	0.813
Flash Point (PMCC)	38°C (Minimum)
Viscosity	1.8
Coverage	30-40 m ² per Litre
Pour Point	<-5°C

Application

- Formwork surfaces to be treated with **logco-lease QD** should be clean and dry.
- **logco-lease QD** should be applied as a thin even film using low pressure spray equipment and any excess material should be removed up prior to placement of the concrete.
- New and unsealed timbers should be pre-treated with **logco-lease QD** with a second application prior to use.

Advantages

- Quick drying release agent suitable for most types of formwork.
- Extremely economical due to the large coverage rates achieved when applied by spray equipment.
- Recommended for difficult and intricate casting work.
- Is not affected by rain.
- The evaporative carrier used in **logco-lease QD** ensures a safe walking surface on soffit formwork with no contamination of the reinforcement.
- Prior to the application of subsequent treatments, concrete that has been cast using **logco-lease QD** requires only a light brush.

Health & Safety

- ▲ When working with **logco-lease QD** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ For further health and safety information, please refer to the relevant Safety Data Sheet.

logco-lease QD

Storage

- **logco-lease QD** should be stored under dry, frost-free conditions away from direct sunlight.
- Under these such conditions the shelf life is at least twelve months.

Packaging

logco-lease QD is available in 20, 25 and 200 Litre Containers.

IBC's available on request.

Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light

of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
Tel: 0113 216 8822
e-mail: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
Tel: 0113 216 8822
e-mail: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd
Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK
Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: sales@logco.co.uk, technical@logco.co.uk
www.logco.co.uk



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.