

# logco resinklens

*Resinklens is a solvent for cleaning resin products from tools, equipment and various surfaces*

## Product Description

**logco-resinklens** is a solvent for cleaning resin from tools, equipment and various other surfaces, preferably before the resin has cured. It can also be used for removing any residual release agent from formwork.

## Technical Data

Appearance	Clear liquid, low viscosity
Specific Gravity @ 15.6c	0.9
Flash Point (PMCC)	38°C

## Packaging & Storage

**Logco-resinklens** is available in 5, 20 & 25 litre containers. Store under dry, frost free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

## Technical Services

**Logco's** Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

**Technical Helpline**  
Tel: 0113 216 8822  
e-mail: [technical@logco.co.uk](mailto:technical@logco.co.uk)

## Sales Enquiries

**Logco** products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

**Sales Team**  
Tel: 0113 216 8822  
e-mail: [sales@logco.co.uk](mailto:sales@logco.co.uk)

**Leeds Oil & Grease Co. Ltd**  
Cliffdale Road, Leeds, West Yorkshire, LS7 2JF, UK  
Tel: 0113 216 8822 Fax: 0113 216 8833 e-mail: [sales@logco.co.uk](mailto:sales@logco.co.uk), [technical@logco.co.uk](mailto:technical@logco.co.uk)  
[www.logco.co.uk](http://www.logco.co.uk)

## Application

When removing resin from tools, clean with RESINKLENS immediately after use before the resin has hardened. If removing old resin, work in RESINKLENS with a rag or stiff brush to remove any resin. When removing any residual release agent from formwork, the surface should be wiped with a rag soaked in RESINKLENS. When complete the surfaces should be wiped over with a clean dry cloth.

When using epoxy mortars, RESINKLENS should be used to wipe over the float face to assist in obtaining a good smooth finish.

## Health & Safety

- ▲ When working with **logco-resinklens** suitable protective clothing, eye/face protection and gloves should be worn.
- ▲ For further health and safety information, please refer to the relevant Safety Data Sheet.