

Product Description

Eco cure Wax is a white, water based low viscosity wax emulsion, which when spray applied to the surface of fresh concrete forms a clear film on drying. eco-cure wax will greatly increase concrete curing efficiency, by retaining moisture, enhancing cement hydration thus providing a stronger, more durable concrete. Suitable for all concreting particularly for large areas, floors & carriageways.

Application

- Eco cure Wax is supplied as a ready to apply product using spray equipment producing a fine mist without damaging the emulsion.
- Spray equipment suitability should be trialed before full application.
- The recommended coverage rate is 4.0 to 5.0 m²/litre.
- Eco cure Wax must be removed from the concrete surface before application of a subsequent coating.
- Eco cure Wax will be slowly removed by everyday foot traffic. To ensure complete removal use water jet, high pressure steam or light sand blasting.

Technical Data

Appearance	Low viscosity white liquid
Specific Gravity @ 15.6c	0.969
Flash Point (PMCC)	Water-based N/A
Viscosity cSt @ 40°C	2.204
Coverage	4-5m ² /litre
Recommended Dilution	None required

Advantages

- Significantly improved curing of concrete.
- Water based, non-flammable.
- Provides a stronger, more durable concrete.
- Exceeds the 90% curing efficiency index (in-house test).
- Spray application, reduces labour costs.
- Single component, i.e. no mixing involved.

Packaging

Eco cure Wax is available in 5, 20, 25 and 200 Litre Containers. IBC's available on request.

Storage

Eco cure Wax should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Health & Safety

When working with Eco cure Wax suitable protective clothing, eye/face protection and gloves should be worn.

For further health and safety information, please refer to the relevant Safety Data Sheet.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
0113 216 8811
E: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
0113 216 8811
E: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales@logco.co.uk | www.logco.co.uk

