

Product Description

Forlease XS is a chemical release agent for use on formwork and moulds to provide easy release and a superior concrete surface finish. It is a blend of reactive oils in a partially evaporative hydrocarbon carrier leaving the remainder of the carrier to form a positive barrier between the form face and the concrete. The release properties of this barrier is further enhanced when soaps are formed by the reactive oils combining with free limes in the concrete. It gives a fast drying capability.

Application

- Forlease XS is supplied ready for use. It should never be diluted and should be applied as thinly and evenly as possible in order to optimise its performance.
- Forlease XS can be applied to all types of formwork by spray, brush, swab or roller—best results are achieved by low pressure spray equipment. Any excess should be removed by swab.
- If using Forlease XS on new or unsealed timber formwork pre-treatment is recommended with a second coat applied prior to use.

Technical Data

| | |
|--------------------|----------------------------|
| Appearance | Low viscosity liquid |
| Colour | Amber |
| Flash Point (PMCC) | 38°C |
| Specific Gravity | 0.81 |
| Viscosity @ 40°C | 1.80 |
| Average Coverage | 40-60m ² /litre |

Health & Safety

When working with Forlease XS suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.

Advantages

- Suitable for use on all types of formwork in all climatic conditions.
- Double action provides a physical barrier and chemical release properties.
- Reduces form cleaning time to a minimum.
- Minimises blowhole and blemishes.
- Inhibits rust formation on steel forms.
- Provides uniform stain-free concrete surfaces.
- Resistant to removal by rain showers and foot traffic.
- Will not impair the bond of any subsequent treatments to concrete.
- Light spray mist coat provides excellent economic usage.

Packaging

Forlease XS is available in 5, 20, 25 and 200 Litre Containers. IBC's available on request.

Storage

Forlease XS should be stored in a cool, well-ventilated area. The container should be kept tightly closed and away from all sources of ignition. Storage life – Unlimited in sealed containers when stored as recommended.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
0113 216 8811
E: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
0113 216 8811
E: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales@logco.co.uk | www.logco.co.uk

