

## Logco Form Seal

Polyurethane Formwork Coating

#### Product Description

Logco Form Seal is a polyurethane coating specifically formulated to give formwork an impervious and protective finish. Logco Form Seal is designed for sealing and protecting general formwork enabling multiple re-use. It will leave a tough, flexible coating improving the life expectancy of the formwork. Quick drying and applied by brush or roller.

## Application

- All surfaces must be clean and untreated.
- Fill all holes and imperfections with Logco Formwork Repair.
- Apply an even coat of Logco Form Seal with a brush or roller to the face and edge preferably with the form horizontal.
- Apply a second coat 1-4 hours later or as soon as the first coat is dry.
- If applying a second coat more than 12 hours later, lightly sand the first coat prior to the second application.
- Stack formwork separately in a well ventilated area.
- Allow to cure for at least 48 hours before use.
- Clean all equipment with Logco Sitewash.

#### 🕕 Technical Data

Appearance	Low viscosity clear liquid
Specific Gravity	0.97
Flash Point (PMCC)	47°C min
Viscosity	Brushing consistency
Coverage	7-9m² per litre
Recommended Dilution	None required

#### 🕕 Advantages

- Single coat application.
- Easy to apply by brush or roller.
- Improves formwork release.
- Life of formwork greatly increased.
- Provides a uniform surface and eliminates moisture absorption.
- Stripping and cleaning time of formwork greatly reduced.

### Packaging

Logco Form Seal is available in 1, 5 and 25 litre cans.

## Storage

Unopened containers of Logco Form Seal should be stored under dry, frost-free conditions away from direct sunlight.

#### 🕕 Shelf Life

12 months when stored in original, unopened packaging.



# Logco Form Seal Polyurethane Formwork Coating

#### Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditons of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relaxing to each product has not been superseded.

#### **Technical Services**

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

**Technical Helpline** 0113 216 8811 E: technical@logco.co.uk

#### **Sales Enquiries**

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team 0113 216 8811 E: sales@logco.co.uk

#### Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales logco.co.uk | www.logco.co.uk



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy him/herself by prioritising that the product is suitable for his/her specific application, and no responsibility can be accepted, or any waranty given by our Representatives, Agents or Distributors.