

Product Description

Logco Hardseal is a low viscosity, penetrating colourless sealer and is based on a carefully sourced blend of chemicals. It hardens, cures and seals and is resistant to oil and fuel.

Logco Hardseal will greatly increase concrete surface anti-abrasion properties particularly on warehouse/factory floors, concrete carriageways and spillway aprons.

Application

- Logco Hardseal is supplied as a ready to apply product by brush or non-atomising spray.
- Do not over apply and brush out any runs that may occur.
- After about 20 minutes the sealer should have soaked into the concrete, and then further coats should be applied until no more material is absorbed.
- Allow 2 to 3 hours to elapse between coatings. Normally 2 coatings are sufficient but on 3 coatings may be needed on very porous surfaces.
- Use only in well ventilated areas and away from sources of ignition.

Technical Data

Appearance	Low viscosity clear liquid
Specific Gravity @ 15.6c	0.911
Flash Point (PMCC)	43°C
Viscosity cSt @ 40°C	N/A
Coverage	5-8m ² per litre
Recommended Dilution	None required

Advantages

- Protects many surfaces from abrasion and water penetration.
- Consolidates floor surfaces.
- Can be used on both interior and exterior brickwork, masonry, reinforced concrete, concrete floors floor screeds, pavements and car parks.
- Single component, ie no mixing involved.
- Can be used both internally and externally.
- 90% minimum curing efficiency.

Packaging

Logco Hardseal is available in 5 , 20, 25 and 200 Litre Containers. IBC`s available on request.

Storage

Logco Hardseal should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months, if unopened.

Once opened replace lid immediately after use and use within 2 weeks.

 **Health & Safety**

When working with Logco Hardseal suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.

 **Important Note**

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
0113 216 8811
E: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
0113 216 8811
E: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales@logco.co.uk | www.logco.co.uk

