

## Product Description

Logco cure Sealer PF a clear acrylic polymer resin solution for application to surfaces of freshly laid concrete floors that have been finished by power floating. It has a double function, firstly to form a highly effective curing membrane that acts as a penetrating sealer for the hardened concrete. It gives a surface that is dustproof and extremely hard wearing.

## Application

- Do not dilute Logco cure Sealer PF.
- Apply by fan-jet sprayer to achieve a typical coverage of 12m<sup>2</sup> per litre immediately after final finishing and surface water is no longer evident.
- Avoid over application, avoid material to form “puddles” but just to leave a wet gloss appearance.
- Pump pressure should be maintained at a level producing a fine spray.
- Clean fine and nozzle thoroughly with solvent cleaner immediately after spraying.

## Technical Data

Appearance	Clear
Coverage	5-6m <sup>2</sup> per litre will generally be sufficient
Packaging	5, 20, 25 or 200 litre containers. IBC's available on request.
Storage	Flash point 38°C Store away from sources of heat
Shelf Life	1 year in sealed container when stored as recommended

## Advantages

- Curing and sealing in one operation saving time and labour.
- Touch dry within 2-6 hours.
- Curing efficiency 75%.
- Provides abrasion resistant hard wearing easy-clean surface.
- Ready to use, easy to spray application.

## Health & Safety

When working with Logco cure Sealer PF suitable protective clothing, eye/ face protection and gloves should be worn.

Areas where this product is being applied must be well ventilated. For further health and safety information, please refer to the relevant Safety Data Sheet.

 **Important Note**

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

**Technical Services**

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline  
0113 216 8811  
E: [technical@logco.co.uk](mailto:technical@logco.co.uk)

**Sales Enquiries**

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team  
0113 216 8811  
E: [sales@logco.co.uk](mailto:sales@logco.co.uk)

**Leeds Oil & Grease Co. Ltd.**

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: [sales@logco.co.uk](mailto:sales@logco.co.uk) | [www.logco.co.uk](http://www.logco.co.uk)

