

### Logco cure Sealer Concrete Curing & Sealing Compound for Floors

Product Description

Logco cure Sealer is a clear acrylic polymer resin sealer and is based on a carefully sourced blend of chemicals. It hardens, cures and seals. Will render surfaces dustproof. Logco cure Sealer will greatly increase concrete surface anti-abrasion properties particularly on warehouse\factory floors and is suited to power floated floors.

## Application

- Logco cure Sealer is supplied as a ready to apply product by brush, roller or non-atomising spray. Do not over apply and brush out any runs that may occur.
- On new concrete apply by non-atomising sprayer at a rate of 5-6m<sup>2</sup> per litre ensuring any surface water has evaporated.
- On aged concrete ensure surface is clean and free from contaminates like oil and paint. Apply by sprayer, roller or brush. One coat may be sufficient but on porous surfaces a second coat may be necessary
- Use only in well ventilated areas and away from sources of ignition.

### 🕕 Technical Data

Appearance	Low viscosity clear amber liquid
Specific Gravity @ 15.6c	0.911
Flash Point (PMCC)	43ºC
Viscosity cSt @ 40°C	N/A
Coverage	5-6m²/litre
Recommended Dilution	None required

#### 🕕 Advantages

- Protects many surfaces from abrasion and water penetration.
- Consolidates floor surfaces.
- Curing and sealing in one operation.
- Single component, ie no mixing involved.
- Can be used both internally and externally.

# Packaging

Logco cure Sealer is available in 5, 20, 25 and 200 Litre Containers. IBC's available on request.

# Storage

Logco cure Sealer should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months, if unopened. Once opened replace lid immediately after use and use within 2 weeks. Clean equipment with white spirit.



### Logco cure Sealer Concrete Curing & Sealing Compound for Floors

#### Health & Safety

When working with Logco cure Sealer suitable protective clothing, eye/face protection and gloves should be worn. Areas where this product is being applied must be well ventilated.

For further health and safety information, please refer to the relevant Safety Data Sheet.

## Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditons of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relaxing to each product has not been superseded.

#### **Technical Services**

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline 0113 216 8811 E: technical@logco.co.uk

#### **Sales Enquiries**

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team 0113 216 8811 E: sales∂logco.co.uk

#### Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales @logco.co.uk | www.logco.co.uk



To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy him/herself by prioritising that the product is suitable for his/her specific application, and no responsibility can be accepted, or any waranty given by our Representatives, Agents or Distributors.