

Product Description

Premium grade chemical release agent is a blend of reactive oils in a partially evaporative rapid drying hydrocarbon carrier. The carrier dries to form a barrier coating on the form face which subsequently reacts with alkalis in the concrete to form soaps at the interface. This double action facilitates easy formwork release and high quality concrete finish.

Uses

- Suitable for use on all types of formwork in all climatic condition.
- Untreated timber formwork should be saturated prior to first use.

Application

- Prior to application surfaces should be thoroughly cleaned.
- For timber and other porous formworks two coats of Logco lease Premium should be applied the second coat applied after the first has dried.
- Apply by spraying a very light mist coat.
- Do not over apply as over application is detrimental to surface finish.
- In cold weather it is advisable not remove the shuttering for at least 24 hours after placing and compacting the concrete.

Technical Data

Colour	Amber
Coverage	30-50 sq.mts per litre depending on surface porosity

Benefits

- Double action provides superior concrete surface finish.
- Recommended for use in confined or poorly ventilated areas.
- Stain-free, suitable for use with white or standard OPC concrete finish.
- Facilitates maximum re-usage of all types of formwork.
- High coverage rate provides economic usage.
- Quick drying on forms to provide cleaner and safer working surfaces.
- Will not impair the bond of any subsequent treatments to concrete.

Packaging

Logco lease Premium is available in 5, 20, 25 litre bottles and 210 litre drums. IBC's available on request.

Storage

Logco lease Premium should be stored in a cool, well ventilated area. Keep away from sources of ignition.

Shelf Life

Practically unlimited in sealed containers.

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
0113 216 8811
E: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
0113 216 8811
E: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales@logco.co.uk | www.logco.co.uk

