

Product Description

Black Bitumen Paint for use as a protective coating for metal work, pipes, tanks etc. Can be used for coating a wide variety of substrates including metal, concrete, stone and asbestos. The dry coating is waterproof and weatherproof.

Application

- The surface to be coated should be dry, sound and free from grease, oil, dust, flaking paint, etc.
- Metal surfaces to be coated should be wire brushed to remove rust.
- It may be advantageous to apply a coat of an anti-corrosive primer before applying Black Bitumen Paint.
- Black Bitumen Paint can be applied by brush, roller or spray.
- The paint may be diluted with white spirit in order to adjust the viscosity for spraying.
- Two coats are recommended on new work.
- Do not apply over tar based products or surfaces that can rise above 65°C.
- Material should be stored out of direct sunlight at 8-25°C.

Technical Data

Appearance	Black paint
Specific Gravity @ 15.6°C	0.89-0.92 at 20°C
Flash Point (PMCC)	32°C min (closed cup)
Viscosity cSt @ 25°C	2.6-3.5P (cone and plate)
Coverage	10m ² /litre on smooth surface
Solids Content	56 +/- 1%
Drying Time	2-4 hours at 20°C

Packaging

Black Bitumen Paint is available in 5, 25L, containers

Storage

Store undercover and protect from frost. Keep container closed, Shelf life uno-pened is at least 12 months.

Health & Safety

When working with Black Bitumen Paint suitable protective clothing, eye/face protection and gloves should be worn.

For further health and safety information, please refer to the relevant Safety Data Sheet

Important Note

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

Technical Services

Logco's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical Helpline
0113 216 8811
E: technical@logco.co.uk

Sales Enquiries

Logco products are distributed throughout the UK through selected stockists and distributors.

Please contact the relevant Customer Services Team below for all product orders and enquiries.

Sales Team
0113 216 8811
E: sales@logco.co.uk

Leeds Oil & Grease Co. Ltd.

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | West Yorkshire | HX5 9DF

0113 216 8811 | E: sales@logco.co.uk | www.logco.co.uk

