Issue 1 06/11/2023

ECOCURE WW

Eco Concrete Curing Compound & Tinted Grade

PRODUCT DESCRIPTION

Environmentally friendly concrete curing membrane. A blue grade version is also available to help in identification during application.

TECHNICAL DATA

Clear or tinted blue
5-6 sq.mts per litre should be sufficient
210 litre drum, 25 litre bottle
Store in dry, frost free conditions. Away from
neat and direct sun light. Keep containers
ightly closed
1 year in sealed container when stored as
recommended

USES

- Locks in moisture into freshly cast concrete surfaces to prevent premature drying out.
- Reducing the risks of surface cracking and dusting.
- The tinted version allows areas to be easily identified.
- The dye breaks down on exposure to UV light and will not permanently discolour the concrete.

ADVANTAGES

- Economical and easy to use.
- Tinted grade available to assist identification during application.
- Prevents premature drying out of the concrete surface reducing the risks of surface cracking and reducing the risk of surface dusting
- Improves the durability of the concrete surface.
- Silane compatible, guaranteed not to adversely affect the bond of subsequent coatings, screeds or renders.

APPLICATION

For freshly cast surfaces:

- Apply as soon as final tamping or trowelling has been finished.
- If surface water is present a second application is desirable as soon as the surface water has evaporated.
- Make sure the correct rate is used to avoid ponding as it may glaze the surface of the concrete.

For surfaces struck from shuttering:

Flood coat with water as soon as the formwork is struck, apply

U-Che Chemical Compounds for Construction

the chosen grade as soon as the water has run off.

- If this is not carried out it is possible that the curing compound will be "sucked" below the concrete surface leaving the surface unprotected.
- If the Tinted grade has been used UV light may not be able to act upon the "fugitive dye" thus leaving the concrete with a permanent colour.
- This advice is applicable whatever grade you may be using.

Note: Care should be taken that over spray does not get onto paint or glass as it may cause permanent damage if not rinsed off immediately.

HEALTH & SAFETY

When working with ECOCURE WW suitable protective clothing, eye/face protection and gloves should be worn.

IMPORTANT NOTICE

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.

www.logco.co.uk

Unit B8 | Lowfields Business Park | Warhurst Road | Elland | HX5 9DF

0113 216 8811 0113 216 8833

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors.