

POLYSTYRENE DISOLVER



PRODUCT DESCRIPTION

Polystyrene Disolver is specially formulated solvent developed to safely dissolve away and emulsify unwanted expanded polystyrene box outs, void formers and inserts. Simply apply Polystyrene Disolver to the expanded polystyrene and observe as the material visibly eats away and dissolves the expanded polystyrene without adversely affecting the surrounding concrete.

TECHNICAL DATA

Appearance	Pale straw, low viscosity liquid
Density @ 15°C	0.9

APPLICATION

- Use in a well ventilated area.
- By far the easiest method of application is to apply Polystyrene Disolver to the unwanted expanded polystyrene by brush although other methods can be used.
- Apply carefully as only small quantities of Polystyrene Disolver are necessary to dissolve quite large volumes of expanded polystyrene.
- Whilst the residue is still in liquid form wash off with clean water and wipe with a damp cloth.
- If residue has not been cleaned off promptly and it has solidified simply re-activate by reapplying Polystyrene Disolver and clean off promptly with clean water.

CLASSIFICATION

- Flammable material with a flash point around 38°C.

PACKAGING

- Available in 5 and 25 litre containers.

IMPORTANT NOTICE

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information relating to each product has not been superseded.